

• Serie 22500 E ASC Plus  
• Serie 27500 E ASC Plus

• Serie 27700 S ASC Plus  
• Serie 28200 E ASC


• Serie 34000 E ASC Plus  
• Serie 39000 E HP




## CRANE SERIE 39000 E HP - SELECT THE MODEL:

- E3
- E4
- E5
- E6
- E7
- E8
- E5F62
- E5F63
- E5F64**
- E6F62
- E6F63
- E6F64

### CRANE E5F64 - CAPACITY DIAGRAM



### CRANE E5F64 - TABLE OF DIMENSIONS



### CRANE E5F64 - INFORMATION SHEET

TECHNICAL CHARACTERISTICS	METRIC SYSTEM	IMPERIAL SYSTEM
Static moment at tower pin	38700 daN/m	279971 lbs/ft
Hydraulic reach	24400 mm	80'1"
Length	1220 mm	4'
Width	2550 mm	8'4"
Height	2450 mm	8'
Weight (without oil and assembly)	4770 kg	10516 lbs
Capacity	2430 kg	5357 lbs
Reach with manual extensions		
Slewing torque	3700 daN/m	26767 lbs/ft
Stabiliser protrusion	1500 + 1750 mm	4'11" + 5'9"
Stabiliser width	5630 mm	18'6"
Pump capacity	60 l/min	16 US gal/min
Pressure	315 bar	4479 psi
Tank capacity	160 l	42 US gal

**DOWNLOAD THE FULL BROCHURE - PDF**


### CRANE E5F64 - SUPPLIED AS STANDARD

- 360° rotation
- Hydraulically extendible base crane stabilisers
- Supplementary control disabled (1)
- Remote control
- HP Continuous acceleration control
- Moment limiter
- Heat exchanger

### CRANE E5F64 - OPTIONAL

- 400° rotation
- Continuous rotation
- Rotating base crane stabilisers
- Extra-wide base crane stabilisers
- Fixed auxiliary crossbeam
- Extendible auxiliary crossbeam
- Supplementary control enabled (1-2)
- Elevated operating position
- Dual moment limiter
- Winch
- Basket
- Self-levelling platform
- Marine crane treatment
- Extended support plates
- Remote control stabiliser check.

### STANDARD SERIE 39000 E HP PHOTO GALLERY



**INFORMATIVA**

Noi e terze parti selezionate raccogliamo informazioni personali come specificato nella privacy policy e utilizziamo cookie o tecnologie simili per finalità tecniche e, con il tuo consenso, anche per le finalità di **funzionalità, esperienza e misurazione** come specificato nella cookie policy.

Puoi liberamente prestare, rifiutare o revocare il tuo consenso, in qualsiasi momento, accedendo al pannello delle preferenze. Il rifiuto del consenso può rendere non disponibili le relative funzioni. Usa il pulsante "Accetta tutto" per acconsentire.

● Funzionalità  
● Esperienza  
● Misurazione

**RANGE**

T-DUTY RANGE  
M-DUTY RANGE  
Y-DUTY RANGE  
SCOPIC CRANES  
BY CRANES  
ANCE INDUSTRY  
ES  
INDUSTRY CRANES  
NE CRANES

**COMPANY PROFILE**

HOME  
ABOUT US  
OUR TECHNOLOGY  
VIDEOS  
DEALERS  
WORK WITH US  
CONTACT US  
RESERVED AREA

**CORMACH SRL**

Via Madonna, 27 CP 199 - 25018 Montichiari (BS) - Italy  
Telefono: +39.030.9656811 (6 linee r.a.) - Fax: +39.030.9656846  
Email: [info@cormach.it](mailto:info@cormach.it)  
P.IVA 00681780987 - C.F. 02075000170  
Reg. Imp. BS: 02075000170 - REA BS: 291719

PRIVACY | COOKIES | WHISTLEBLOWING  
Web design: [Studio Imprints](#)