50000 WB95

DIMENSIONS

50000 WB95

63.0 TM	Ton Meter Rating
464,663 ft lbs	Foot Pound Rating
95' 2"	Horizontal Hydraulich Reach
106' 6"	Approx. Vertical Reach
1,322 lbs @95' 2"	Horizontal Lifting capacity excluding weight of fork
1,455 lbs @87' 10"	
1,610 lbs @80' 10"	
1,830 lbs @74' 2"	
2,138 lbs @67' 8"	
3,350 lbs @55' 5"	
6,130 lbs @41' 1"	
3	Hydraulic Extensions Main Boom
4	Hydraulic Extensions Outer Boom
360° Continuous	Crane Rotation
Brg. Ring & Pinion	Crane Rotation Type
2 each side of operators seat arm plus 3 foot pedals	Control Levers – and – Control Location
DANFOSS	Main Control Valve Type
Option	Radio Remote Control System
4,640 PSI	Max. Operating Hydraulic Pressure
	Hydraulic Piston Pump Type Required
	Variable Displacement – Load Sensing
26 GPM	Pressure Compensating
66 Gal	Hydraulic Reservoir Capacity
Option	Oil Cooler
Electro-Hydraulic	Lod Limiting Device Type
25 feet	Main Crane Base Outrigger Span
19' 2"	Auxiliary Rear Outrigger Span
4 Included	Oversize Outrigger Ground Plates
45"	Crane Mounting Space Required
Included	Operators Walk Around Platform and Acces ladder
14,130 lbs	Crane Weight Incl. Mount Bolt Kit, & Operators Platform
110"	Stowed Height Of Crane Above Sub Frame In Travel Position
78½" x *74½"	Cargo Space Between Body Surface and Underside Of Boom

* Under knuckle only

Capacity, specifications and dimensions may change without notice