


Ausladung und Hubhöhe • Radius and hoisting height • Portée et hauteur de levage
 Sbraccio e altezza di sollevamento • Alcance y altura de elevación • Alcance e altura de elevação
 Вылет и Высота подъема



Minimum Ausladung außer Betrieb • Minimum radius out of operation • Portée minimum hors service • Sbraccio minimo fuori servizio • Alcance mínimo fuera de servicio • Alcance mínimo fora de operação • Минимальный вылет вне работы

Ausleger (m) • Jib • Flèche
 Braccio • Pluma • Lança • Стрела

Außerbetriebsstellung (α°) • Out-of-operation position • Position hors service • Posizione fuori servizio
 Posición externa de la empresa • Posição fora de operação • Положение вне работы

	α	C (m)	C (m)
60	73°	19,7	-
55	74°	17,3	16,8
50	74°	15,9	15,4
45	74°	14,4	14,0
40	72°	14,3	13,9
35	70°	13,9	13,4
30	68°	13,1	12,6

Ausladung und Tragfähigkeit • Radius and capacity • Portée et charge • Sbraccio e portata Alcances y cargas • Alcance e capacidade de carga • Вылет и грузоподъемность

m			t	m																		
				15,0	17,5	20,0	22,5	25,0	27,5	30,0	32,5	35,0	37,5	40,0	42,5	45,0	47,5	50,0	52,5	55,0	57,5	60,0
60,0		3,2 - 29,0	8	8,00						7,68	6,95	6,31	5,75	5,24	4,79	4,37	4,00	3,65	3,33	3,04	2,77	2,50
		3,2 - 28,3	8	8,00						7,45	6,72	6,09	5,52	5,02	4,57	4,16	3,79	3,44	3,13	2,84	2,57	2,30
55,0		3,1 - 25,9	10	10,00					9,37	8,50	7,74	7,07	6,46	5,92	5,43	4,98	4,57	4,20	3,84	3,50		
		3,1 - 25,2	10	10,00					9,09	8,23	7,48	6,82	6,22	5,69	5,21	4,76	4,36	3,99	3,64	3,30		
		2,7 - 18,0	14	14,00	12,65	11,25	10,08	9,08	8,22	7,47	6,80	6,20	5,66	5,17	4,73	4,32	3,94	3,59	3,30			
50,0		3,0 - 27,9	10	10,00					9,21	8,38	7,65	7,00	6,41	5,87	5,38	4,93	4,50					
		3,0 - 27,2	10	10,00					9,88	8,92	8,09	7,36	6,71	6,14	5,62	5,15	4,71	4,30				
		2,6 - 17,0	16	16,00	15,57	13,70	12,18	10,90	9,82	8,89	8,07	7,34	6,69	6,10	5,57	5,09	4,64	4,30				
45,0		2,9 - 29,6	10	10,00					9,84	8,94	8,15	7,44	6,81	6,24	5,70							
		2,9 - 28,9	10	10,00					9,57	8,68	7,90	7,21	6,59	6,03	5,50							
		2,5 - 16,8	18	18,00	17,28	15,08	13,31	11,86	10,63	9,58	8,66	7,86	7,15	6,51	5,93	5,50						
40,0		2,8 - 30,8	10	10,00						9,37	8,54	7,80	7,10									
		2,8 - 30,2	10	10,00						9,14	8,32	7,59	6,90									
		2,4 - 17,8	18	18,00	15,96	14,07	12,51	11,20	10,08	9,10	8,24	7,47	6,90									
35,0		2,7 - 31,5	10	10,00						9,65	8,80											
		2,7 - 30,9	10	10,00						9,44	8,60											
		2,3 - 18,5	18	18,00	16,59	14,60	12,96	11,58	10,40	9,36	8,60											
30,0		2,6 - 30,0	10	10,00																		
		2,6 - 30,0	10	10,00																		
		2,2 - 19,3	18	18,00	17,32	15,20	13,45	11,97	10,90													

""reine 1-Strang Unterflasche (10 t) • single-fall bottom hook block (10 t) • moufle inférieure à brin unique (10 t) • bozzello ad 1 rinvio (10 t) • polipasto inferior con un ramal (10 t)
moitão de carga com uma queda de cabo (10 t) • Нижняя крюковая обойма с 1-кратной запасовкой (10 t)

Tragfähigkeiten gültig bis 100 m Hubhöhe. Über 100 m Hubhöhe reduziert sich die Tragfähigkeit um das zusätzliche Seilgewicht. • Lifting capacities valid up to 100 m hoisting height. Over 100 m hoisting height, the lifting capacity is reduced by the additional rope weight. • Capacités de levage valables jusqu'à 100 m de hauteur sous crochet. Au-dessus de 100 m de hauteur sous crochet, la capacité de levage est réduite du poids de câble supplémentaire. • Portate valide fino a 100 m d'altezza di sollevamento. Oltre i 100 m si riduce la portata causa il peso addizionale della fune. • Cargas válidas hasta altura de 100 m. Por encima de los 100 m se reduce la carga por el peso adicional del cable. • Cargas válidas até à altura de 100 m. Para além dos 100 m, reduz-se a carga pelo peso adicional do cabo. • Грузоподъемность действительна до 100 м высоты подъема. Свыше 100 м высоты подъема грузоподъемность сокращается на вес дополнительного каната.