





Dimensions and weight

Slewing crane part:  262 ft -  320 LVF



Slewing crane part		L (ft)	W (ft)	H (ft)	Ib (+/- 5%)	
Counter-jib		38.4	15.4	6.4	14,551	
		36.2	12.3	6.8	10,858	
Cathead		11.6	6.5	32.3	18,221	
Cab	Ultra View	16.4	8.2	9.1	4,134	
Towerhead	8 ft	12.1	9.5	12.7	24,670	
Hoisting winch (+ rope)	320 LVF	16.7	7.5	7.3	21,793	
Intermediate winch frame		10.7	9.5	5.4	12,485	
Jib section		①	34	6.2	8.3	11,244
		② 15 DVF	33.9	6.2	7.7	11,442
		③	33.6	6.2	7.9	6,636
		④	33.6	6.2	7.6	6,107
		⑤	33.6	6.2	7.6	6,250
Jib section		⑧	33.5	6.2	6.6	3,075
		⑥	17.5	6.2	7.4	3,803
		⑦	17.2	6.2	6.7	2,381
		⑨	17	6.2	6.5	1,213
Trolley		⑩	16.7	6.2	6.5	1,102
			6.4	7.3	5.5	1,731
Pulley block		5.5	0.9	8	1,257	

Crane Tower	L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Telescopic cage T 851 	8 ft	36.7	15.9	19 34,723
K 84/K 84-2 Telescoping mast 	8 ft	7.3	10.6	8.2 6,724
KRM 849B KMT 849A KR 849A KRMT 849A KRMT 849C 	8 ft	33.6 17.2 17.2 17.2 11.7	8.4 8.4 8.3 8.4 8.4	8.3 8.3 8.2 8.3 8.3 17,196 6,945 9,458 9,017 7,066
Fixing angles 	P 63A / P 800B	2.5	2.5	4.2 1,025
1/2 Cross girder 	ZY 800	18.6	3.2	6.3 10,406
Cross girder 	ZY 800	39.2	4.6	6.3 22,212