



















Dimensions and weight

Slewing crane part:  180 ft -  -  -  25 LVF



| Slewing crane part | | L (ft) | W (ft) | H (ft) | lb (+/- 5%) | |
|-------------------------|---|---|--------|--------|-------------|--------|
| Counter-jib |  |  3.9 ft | 39.2 | 6.8 | 8.1 | 12,302 |
| | |  5.2 ft | 39.2 | 7.1 | 8.9 | 12,633 |
| Towerhead + cab |  | Ultra View | 10.4 | 6.5 | 11.9 | 2,194 |
| Jib section |  | ① 25 LVF 6 DVF | 34.8 | 8.8 | 8.6 | 7,253 |
| Jib section |  | ④ | 17 | 3.4 | 6.3 | 886 |
| | | ⑤ | 17 | 3.4 | 6.3 | 756 |
| | | ⑥ | 17 | 3.4 | 6.2 | 756 |
| | | ⑧ | 16.9 | 3.4 | 3.9 | 503 |
| Jib section |  | ② | 33.5 | 3.4 | 7.7 | 3,025 |
| Jib section |  | ③ | 17 | 3.4 | 7.6 | 992 |
| | | ⑦ | 16.9 | 3.4 | 6.2 | 646 |
| Jib section |  | ⑨ | 16.7 | 3.4 | 3.8 | 417 |
| Hoisting winch (+ rope) |  | 25 LVF | 4.4 | 2.3 | 2.3 | 1,687 |
| | | 33 LVF | 4.5 | 3 | 2.9 | 2,127 |
| Trolley |  |  6.6 Ust | 5.2 | 4.4 | 2.9 | 617 |
| Pulley block |  |  6.6 Ust | 3 | 0.9 | 4.3 | 628 |
| Trolley |  |  6.6 Ust | 4.6 | 4.1 | 3.1 | 617 |
| Trolley |  |  6.6 Ust | 4.7 | 4.1 | 3.1 | 617 |
| | |  3.3 Ust | 5 | 4.3 | 3.1 | 518 |
| Pulley block |  |  6.6 Ust | 4.1 | 0.9 | 5 | 551 |
| | |  3.3 Ust | 2.6 | 0.7 | 4.2 | 287 |

| Crane tower | | | L (ft) | W (ft) | H (ft) | lb (+/- 5%) |
|--|---|--|------------------------------|--------------------------|--------------------------|----------------------------------|
| Telescopic cage T 41 |  | □ 5.2 ft | 35.6 | 12.3 | 13.5 | 15,653 |
| K40/K40-2 |  | □ 5.2 ft | 7.3 | 6.9 | 6.8 | 2,932 |
| K 447E KM 447E KM 449E |  | | 33.5 33.5 33.5 | 5.3 5.3 5.3 | 5.3 5.3 5.3 | 7,474 7,088 8,830 |
| K 447A KMT 447A K 449A KMT 449A |  | □ 5.2 ft | 17.1 17.1 17.1 17.1 | 5.5 5.5 5.5 5.5 | 5.3 5.3 5.3 5.3 | 4,079 3,847 4,916 4,696 |
| K 447C KMT 447C |  | | 11.3 11.6 | 5.5 5.5 | 5.3 5.3 | 2,998 2,976 |
| K20/K40 |  | □ 3.9/5.2 ft | 5.6 | 5.4 | 5.4 | 4,189 |
| KM 247E KM 249E |  | □ 3.9 ft | 33.5 33.5 | 4 4 | 4 4 | 7,165 8,818 |
| KM 247A KM 249A |  | | 17.1 17.1 | 4 4 | 4 4 | 3,748 4,630 |
| K40/L20-2 |  | □ 5.2/3.9 ft | 9.7 | 6.8 | 6.9 | 4,630 |
| S 28ES-2 SR 26E-2 SR 28ER-2 |  | | 35.3 35.3 35.3 | 4.2 4.2 4.2 | 4.2 4.2 4.2 | 7,604 6,735 9,050 |
| SR 25F-2 |  | □ 3.9 ft | 25.4 | 4.2 | 4.2 | 4,447 |
| SR 26X-2 |  | | 10.7 | 4.1 | 4.1 | 2,169 |
| Fixing angles |  | P 12D P 12ER P 24A / P 42A | 1.6 2.6 1.8 | 1.6 2.6 1.8 | 3.7 4.3 3.8 | 357 926 529 |
| Basic mast unit |  | S 41A | 11.9 | 6.4 | 6.8 | 7,132 |
| Struts |  | S 41A | 10.4 | 0.9 | 0.8 | 816 |
| Half-bearer |  | S 41A | 16.7 | 2 | 5.8 | 2,315 |
| Cross girder |  | ZC 2030 ZD 2030 ZC 4230 ZD 4230 | 18.5 21.7 18.5 21.8 | 2.7 2.7 2.7 2.7 | 3.8 3.8 3.4 3.4 | 3,307 3,726 3,505 4,035 |
| Cross girder |  | ZC 2030 ZD 2030 ZC 4230 ZD 4230 | 18.5 21.7 18.5 21.8 | 1.5 1.5 1.5 1.5 | 4.8 4.8 4.4 4.4 | 3,825 4,255 4,178 4,707 |