












Dimensions and weight

Slewing crane part:  180 ft -  -  -  -  25 LVF



Slewing crane part		L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Counter-jib		39	3.9	8.2	10,406
Towerhead + cab	Ultra View	14.2	7.4	8	11,890
Jib section	① 25 LVF 6 DVF	35.9	9.6	8.5	7,110
Jib section	② ⑤ ⑥ ⑧	17.2 17 17 16.9	3.4 3.4 3.4 3.4	7.7 6.3 6.2 3.9	1,620 886 756 503
Jib section	③	33.4	3.4	7.7	2,482
Jib section	④ ⑦	17 16.9	3.4 3.4	7.6 6.2	990 646
Jib section	⑨	17	3.4	3.8	417
Hoisting winch (+ rope)	25 LVF 33 LVF	4.3 4.5	2.3 3	2.3 2.9	1,687 2,127
Trolley	 6.6 Ust	5.2	4.4	2.9	617
Pulley block	 6.6 Ust	3	0.9	4.3	628
Trolley	 6.6 Ust	4.6	4.1	3.1	617
Trolley	 6.6 Ust  3.3 Ust	4.7 5	4.1 4.3	3.1 3.1	617 518
Pulley block	 6.6 Ust  3.3 Ust	4.1 2.6	0.9 0.7	5 4.2	551 287

Crane tower		L (ft)	W (ft)	H (ft)	lb (+/- 5%)	
Telescopic cage T41		5.2 ft	35.6	12.3	13.5	15,653
K40/K40-2		5.2 ft	7.3	6.9	6.8	2,932
K 447E KM 447E KM 449E		5.2 ft	33.5 33.5 33.5	5.3 5.3 5.3	5.3 5.3 5.3	7,474 7,088 8,830
K 447A KMT 447A K 449A KMT 449A		5.2 ft	17.1 17.1 17.1 17.1	5.5 5.5 5.5 5.5	5.3 5.3 5.3 5.3	4,079 3,847 4,916 4,696
K 447C KMT 447C		5.2 ft	11.3 11.6	5.5 5.5	5.3 5.3	2,998 2,976
K20/K40		3.9/5.2 ft	5.6	5.4	5.4	4,189
KM 247E KM 249E		3.9 ft	33.5 33.5	4 4	4 4	7,165 8,818
KM 247A KM 249A		3.9 ft	17.1 17.1	4 4	4 4	3,748 4,630
Fixing angles		P 24A / P 42A	1.8	1.8	3.8	529
Basic mast unit		S 41A	11.9	6.4	6.8	7,132
Struts		S 41A	10.4	0.9	0.8	816
Half-bearer		S 41A	16.7	2	5.8	2,315
Cross girder		ZC 4230 ZD 4230	18.5 21.8	2.7 2.7	3.4 3.4	3,505 4,035
Cross girder		ZC 4230 ZD 4230	18.5 21.8	1.5 1.5	4.4 4.4	4,178 4,707