



















Dimensions and weight

Slewing crane part:  197 ft - L-J-132 HPL™



Slewing crane part		L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Counter-jib	 100 VVF	28.3	16.5	19.3	24,482
Strut		23.6	9	37.8	14,440
Cab	 Ultra View	17.1	6.4	8.2	4,079
Towerhead	 6.6 ft	10.2	8.1	9.7	20,944
		17.1	15.7	12.5	25,023
Jib section	 ①	19.3	7.2	6.1	3,086
	 ② ⑤ ⑥ ⑦	33.4	6.2	6.9	3,086
		33.4	6	6.6	2,866
		33.4	6	6.6	2,756
		31	6	6.6	3,086
	 ③ ④	17	6	6.9	2,116
17		6	6.6	1,521	
	5.9	5.1	7.4	959	
Jib nose inspection platform		4.7	2.5	6	187
Pulley block		4.1	1	4.4	342
		2.8	0.9	3.8	1,025
		5.3	1.8	5.6	1,135
	5.3	1.8	7.8	2,160	

Hoisting winch (+ rope)		132 HPL™ 180 HPL™ GH	11.6 15	6.1 6.3	6.2 6.5	11,100 19,103
Luffing winch (+ rope)		100 VVF	10.6	5.5	5.9	7,948
<b>Crane tower</b>			<b>L (ft)</b>	<b>W (ft)</b>	<b>H (ft)</b>	<b>lb (+/- 5%)</b>
T 61 T 851		□ 6.6 ft □ 8 ft	35.5 36.7	13.6 15.9	14.7 19	21,385 34,723
K80/KR60-2 Connecting mast		□ 8/6.6 ft	7.3	10.7	8.1	8,852
K 649B KM 649E KRM 6410B KRM 849B		□ 6.6 ft □ 6.6 ft □ 6.6 ft □ 8 ft	33.6 33.8 33.6 33.6	6.8 6.7 6.9 8.4	6.7 6.7 6.8 8.3	11,663 10,692 15,653 17,196
K 649A KMT 649A KR 649A KRMT 649A K 849A KMT 849A KR 849A KRMT 849A		□ 6.6 ft □ 6.6 ft □ 6.6 ft □ 6.6 ft □ 8 ft □ 8 ft □ 8 ft □ 8 ft	17.2 17.2 17.2 17.2 17.2 17.2 17.2 17.2	6.8 6.8 6.9 6.9 8.3 8.4 8.3 8.4	6.7 6.7 6.8 6.8 8.2 8.3 8.2 8.3	6,184 5,666 7,165 6,724 7,496 6,945 9,458 9,017
K 649C KMT 649C KRMT 649C KRMT 849C		□ 6.6 ft □ 6.6 ft □ 6.6 ft □ 8 ft	11.7 11.7 11.7 11.7	6.8 6.8 6.9 8.4	6.7 6.7 6.8 8.3	4,559 4,542 5,401 7,066
Fixing angles		P 63A / P 800B	2.5	2.5	4.2	1,025
Basic mast unit		V 60A V 63A	16.4 32.9	7.9 7.9	7.9 7.9	10,494 16,887
Struts		V 60A V 63A	14.8 14.8	1 1.1	1 1.1	1,036 1,235
Half-bearer		V 60A V 63A	22 22	2.3 2.3	7.6 7.6	4,057 4,101
1/2 Cross girder		ZX 640	14.3	3.3	5.1	7,319
Cross girder		ZX 640	30	3.9	5.1	15,168

Mechanisms

480 V - 60 Hz													hp	kW	
	132 HPL™ 63	fpm	133	172	243	363	502	67	87	125	185	251	132	98	2,815 ft
		USt	13.8	10.4	6.9	3.4	1.1	27.6	20.7	13.8	6.9	2.9			
	180 HPL™ 63 GH	fpm	179	220	289	438	640	90	112	149	238	320	180	132	3,937 ft
		USt	13.8	10.4	6.9	3.4	0.9	27.6	20.7	13.8	6.9	3.3			
	100 VVF 50		2 min									100	75		
	RVF 172 Optima+	rpm	0 → 0.8									2 x 10	2 x 7.5		

IEC 60204-32		
480 V (+6% -10%) 60 Hz	132 HPL™ + 100 VVF: 205 → 112 kVA 180 HPL™ + 100 VVF: 243 → 131 kVA	

These mast combinations meet the EN 14439 and ASME B30.3-2016 specifications for “out of service” wind conditions, provided the illustrated wind speed matches required design wind speed for the location of the tower crane. The “out of service” design wind speed was determined in accordance with ASCE 7-10, Figure 26.5-1A. The wind velocity, used for this configuration was 98 mph (158 kph), which represents a nominal design 3-second wind gust at 33 ft (10 m) above ground for Exposure B category. A factor of 0.85 was applied to the 700-year ultimate design wind speed of 115 mph (185 kph), per ASCE 37-02, with the assumption that this crane is considered a temporary structure used during a construction period of 2 years or less.

- Standard equipment
- Options
- Potain Plus function: Plus load curves
- Hook heights with Plus load curves
- Reactions in service
- Reactions out of service
- Jib weight
- Total ballast weight
- Jib articulation axis
- Weather vaning position
- Lorry 44 ft
- Container High Cube 40 ft, and/or Flat Rack 20 ft
- Hoisting
- Luffing
- Slewing
- Travelling
- Required power
- Power Control Function: winch speeds adapted to the available power
- Consult us

This commercial document is not legally binding. For any technical information, please refer to the corresponding instructions.

