























Dimensions and weight

Slewing crane part:  262 ft -  -  132 HPL™



Slewing crane part		L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Counter-jib		38.4	13.5	6.4	14,308
		13.8	6.6	6.4	4,365
		36.2	11.7	6.8	10,858
		16.5 18.5	11 10.8	5.5 6.4	1,323 3,541
		132 HPL™ 180 HPL™ GH			
Cathead		11.6	6.5	32.3	18,221
Cab		Ultra View 16.4	8.2	9.1	4,134
Towerhead		17.8 ft	12.1	9.5	25,485
Hoisting winch (+ rope)		12.4 15.8	6.1 6.3	6.2 6.5	11,387 19,279
		132 HPL™ 180 HPL™ GH			
Jib section		① 34	6.2	8.3	11,241
		② 33.9	6.2	7.7	10,944
		③ 33.6	6.2	7.9	6,634
		④ 33.6	6.2	7.6	6,105
		⑤ 33.6	6.2	7.6	6,279
Jib section		⑥ 17.5	6.2	7.4	4,222
		⑦ 17.2	6.2	6.7	2,476
		⑧ 17.2	6.2	6.7	2,314
		⑩ 17	6.2	6.5	1,215
Trolley + Pulley block		5.9	7.4	4.7	1,676
		3.9	1.4	7.8	1,874
Trolley + Pulley block		13.5	7.2	3.8	2,635
		6	1.1	7.7	1,995

Crane Tower		L (ft)	W (ft)	H (ft)	lb (+/- 5%)	
Telescopic cage T 851		8 ft	36.7	15.9	19	34,723
K 85/K 85-2 Telescoping mast		8 ft	7.3	10.7	8.2	7,937
KM 850.10B KM 850.14B KMT 850.10A KMT 850.14A K 88/K 85A2 KM 880.10A KMT 880.10A KMT 850.10C		8 ft	33.9 33.9 17.5 17.5 17.5 17.8 17.8 12	8.3 8.3 8.3 8.3 8.2 8.3 8.3 8.3	8.2 8.2 8.2 8.2 8.2 8.3 8.6 8.2	22,201 24,670 12,015 13,206 18,281 18,453 19,180 9,326
Fixing angles		P 854A P 880A	3 3.3	3 3.3	4.9 6.2	2,072 3,536
Central cross (transport position)		JM 850	17.1	5.6	4.9	14,771
Basic mast unit		JM 850	28.7	8.2	8.2	32,187
Chassis girder		JM 850	17.1	3	5.1	7,055
Chassis ties		JM 850	23.6	0.8	1.1	551
Struts		JM 850	26.9	2.5	4.3	5,071
1/2 Cross girder		ZY 854	18.7	3.2	7.4	14,176
Cross girder		ZY 854	39	4.7	7.4	30,865