









Dimensions and weight

Slewing crane: 262 ft - 132 HPL™



Slewing crane part		L (ft)	W (ft)	H (ft)	lb (+/- 5%)	
Counter-jib		38.4	13.5	6.4	14,308	
		13.8	6.6	6.4	4,365	
		36.2	11.7	6.8	10,858	
	132 HPL™ 180 HPL™ GH	16.5 18.5	11 10.8	5.5 6.4	1,323 3,541	
Cathead		11.6	6.5	32.3	18,221	
Cab	Ultra View	16.4	8.2	9.1	4,134	
Towerhead	8 ft	12.1	9.5	12.7	24,670	
Hoisting winch (+ rope)	132 HPL™ 180 HPL™ GH	12.4 15.8	6.1 6.3	6.2 6.5	11,387 19,279	
Jib section		①	34	6.2	8.3	11,188
		② 10 DVF	33.9	6.2	7.7	10,439
		③	33.6	6.2	7.9	6,625
		④	33.6	6.2	7.6	6,096
		⑤	33.6	6.2	7.6	6,250
⑧	33.5	6.2	6.6	3,064		
Jib section		⑥	17.5	6.2	7.4	3,792
		⑦	17.2	6.2	6.7	2,381
		⑨	17	6.2	6.5	1,213
		⑩	16.7	6.2	6.5	1,102
Trolley	27.6 USt	5.9	7.4	4.7	1,676	
Pulley block	27.6 USt	3.9	1.4	7.8	1,874	

Trolley		27.6 USt	13.5	7.2	3.8	2,635
Pulley block		27.6 USt	6	1.1	7.7	1,995
Crane Tower			L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Telescopic cage T 851		□ 8 ft	36.7	15.9	19	34,723
K 84/K 84-2 Telescoping mast		□ 8 ft	7.3	10.6	8.2	6,724
KRM 849B KMT 849A KR 849A KRMT 849A KRMT 849C		□ 8 ft	33.6 17.2 17.2 17.2 11.7	8.4 8.4 8.3 8.4 8.4	8.3 8.3 8.2 8.3 8.3	17,196 6,945 9,458 9,017 7,066
Fixing angles		P 63A / P 800B	2.5	2.5	4.2	1,025
1/2 Cross girder		ZY 800	18.6	3.2	6.3	10,406
Cross girder		ZY 800	39.2	4.6	6.3	22,212