

TURF TRACER[®] X-SERIES

**THE WALK-BEHIND THAT
IS MILES AHEAD OF THE
COMPETITION.**



By virtually any measure, the Turf Tracer X-Series represents the definitive, full-featured hydro mower. Whether you choose the 52- or 60-inch cutting deck, the UltraCut™ Series 4 with splined spindle blade driver is up to the toughest jobs. As are the X-Series engines—Kohler® EFI, Kawasaki® and Kohler EFI Propane. Ground speeds up to 6.75 mph, and up to 2.25 in reverse, also rank the Turf Tracer X-Series among the most productive mowers in its class.

FEATURES:

- Choose from Kawasaki or Kohler equipped engines.
- UltraCut Series 4 deck with 52-, and 60-inch cutting widths.
- Heavy-duty canister air filtration system.
- Ground speeds up to 6.75 mph.
- Equipped with Exmark's exclusive Enhanced Control System (ECS).



PATENTED ENHANCED CONTROL SYSTEM (ECS)

Recent university tests showed landscape professionals prefer our control system to all others on the market.



SUPERIOR AIR FILTRATION

X-Series Turf Tracers come standard with heavy-duty canister air filtration systems for longer engine life, more efficient performance and simple maintenance.



CLUTCH PERFORMANCE

A large-capacity, electromagnetic PTO clutch provides excellent durability for extra-long life.

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Turf Tracer® are registered trademarks of Exmark Mfg. Co., Inc. ©2015 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2015.

TURF TRACER® X-SERIES

SPECIFICATIONS

MODEL NUMBER	ENGINE	CONTROLS	SIZE	DECK	WEIGHT	LENGTH	HEIGHT	WIDTH DEFL. DOWN	WIDTH DEFL. UP
TTX650EKC52400	ECV650 Kohler® EFI Electric Start	ECS	52"	UltraCut™ Series 4	720 lbs	84.75"	45.0"	64.8"	53.4"
TTX680PKC52400	PCV680 Kohler EFI Electric Start Propane	ECS	52"	UltraCut Series 4	740 lbs	84.75"	45.0"	64.8"	53.4"
TTX691GKA52400	FX691V Kawasaki® V-Twin Electric Start	ECS	52"	UltraCut Series 4	720 lbs	84.75"	45.0"	64.8"	53.4"
TTX650EKC60400	ECV650 Kohler EFI Electric Start	ECS	60"	UltraCut Series 4	760 lbs	84.75"	45.0"	73.0"	61.4"
TTX650EKC604N0	ECV650 Kohler EFI Electric Start	ECS	60"	UltraCut Series 4	840 lbs	104.8"	45.0"	73.0"	61.4"
TTX680PKC60400	PCV680 Kohler EFI Electric Start Propane	ECS	60"	UltraCut Series 4	780 lbs	84.75"	45.0"	73.0"	61.4"
TTX691CKA60400	FX691V Kawasaki V-Twin Electric Start	ECS	60"	UltraCut Series 4	760 lbs	84.75"	45.0"	73.0"	61.4"

POWER COMPONENTS

ENGINES – FX691V Kawasaki V-Twin; ECV650 Kohler® EFI; PCV680 Kohler Command EFI Propane. All engines governed to 3,600 rpm.

AIR FILTER – Heavy-duty canister air filtration system.

DRIVE SYSTEM – Twin Hydro-Gear® variable-displacement pumps and twin high-efficiency Parker/Ross wheel-drive motors with 1" (2.54 cm) tapered shafts.

HYDRO FLUID – Exmark Premium Hydro Oil.

SPEED – Infinitely variable selection from 0–6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.

PTO ENGAGEMENT – MagStop Electromagnetic 200 ft-lbs clutch.

FUEL CAPACITY – 5-gallon (18.9-L) fuel tank. Propane unit has 33.5-lb (8.0 gallon) propane tank.

DRIVE-WHEEL RELEASE – Allows unit movement without engine running.

DECK LIFT – Manual lift with hairpin from hole to hole for position adjustment.

DECKS

STYLE – Full-floating UltraCut™ Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.

WIDTHS AVAILABLE – 52" (132 cm) or 60" (152.4 cm).

DECK CONSTRUCTION – 10-gauge top that is formed and continuously seam-welded, with 10-gauge top reinforcement plate, 7-gauge side skirt and 7-gauge reinforcement rings at spindle assembly. 4-point suspension, full-floating deck with 6 adjustable anti-scalp rollers.

CUTTING HEIGHT – 1.5" (3.8 cm.) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

BLADE SPINDLES – No maintenance, sealed and non-greasable spindles; 7.25"-diameter cutter housing with 1.75"-diameter splined blade drive and 25mm (0.98") diameter spindle shaft.

BLADE-TIP SPEED – Approximately 18,500 fpm.

EQUIPMENT

ENGINE DECK – 7-gauge, heavy-duty welded steel.

STEERING AND MOTION CONTROL – Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.

CASTERS – .38" thick caster yoke arms.

FRONT CASTER TIRES – Double-yoke, 11 x 4.0-5, smooth tread, semi-pneumatic.

DRIVE TIRES – 18 x 8.5-8, 4-ply Turf Master.®

TRACKING ADJUSTMENT – Insta-Track.

TURNING RADIUS – True zero-turn.

SAFETY PACKAGE – Operator Presence Controls (OPC). Operator must have speed control lever in neutral and blades disengaged to leave operator's position without stopping engine.

PARKING BRAKE – Lever-actuated mechanical compression.

ELECTRICAL SYSTEM – 12-volt battery, 15-amp alternator, except for Kohler EFI has 20-amp alternator.

ENGINE HOUR METER – Standard.

ACCESSORIES & OPTIONS

3-Bushel Bagger, Equipment Cover, Mulching Kit, Operator Controlled Discharge, StandOn and Turf Striping Kit.

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Turf Tracer® are registered trademarks of Exmark Mfg. Co., Inc. ©2015 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2015.