


HUSQVARNA Z572X

The Husqvarna Z500 series zero turn mower represents the latest design focused on productivity, durability and cut quality. Providing extreme comfort, high ground speeds and superior traction adds up to exceptional mowing efficiency. Industrial strength throughout the entire design assures a long & durable service life in commercial mowing applications. Careful design consideration provides unprecedented ease in serviceability.



LED fuel gauge

The automotive style LED fuel gauge lets you know exactly how much fuel is remaining and warns you when you are too low.



AGM Battery

A smaller and more robust battery adopted from the transportation industry provides better reliability, improved longevity and more service space.

Cast aluminium spindles

10" diameter commercial cast aluminium spindles with tapered roller bearings more effectively spread impact loads for extended durability.



Heavy duty fabricated cutting deck

A deep draw deck, heavy duty cutting blades and an efficient flow design allow for rapid cut speeds with a high quality finish.



FEATURES

- Cast aluminium spindles
- AGM Battery
- Automotive style LED fuel gauge
- Heavy duty fabricated cutting deck
- Automatic parking brake
- The discharge chute is built of heavy-duty rubber to withstand wear and tear while protecting nearby property.
- HydroGear ZT5400 Transmissions handles even the biggest jobs in landscaping
- Deck height adjustment
- Easily foldable ROPS protects the user
- Large fuel capacity
- Comfortable, user-focused controls put everything needed to operate the mower within easy reach.
- Premium suspension seat for increased comfort

Technical Specifications	
BATTERY	
Battery capacity	12 Ah
Battery pack weight	3.1 kg
Battery type	Lead-Acid
Battery voltage	12 V
Cells per battery	6
Quantity of batteries/battery pack	1 pcs
Weight of one battery	6.83 lbs
CAPACITY	
Blade-tip speed	93.98 m/s
Net power at preset rpm	3600 rpm
Power output	31 hp
CERTIFICATIONS	
Clutch rating	338.95 Nm
Power rating	23117 W
DIMENSIONS	
Article gross weight	752510 g
Article net weight	616432 g
Base machine, height (ROPS down)	117 cm
Base machine, height (ROPS up)	185 cm
Base machine, height	117 cm
Base machine, length	206 cm
Base machine, width (chute down)	219.1 cm
Base machine, width (chute up)	198.76 cm
Base machine, width	136 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Manual
Cutting height steps	16
Deck thickness	4.76 mm
Handle height adjustment	Yes
Seat back height	High
Weight	616.4 kg
ENGINE	
Cylinder displacement	999 cm ³
Cylinders	2
Engine cooling	Air
Engine name	FX Series
Motor/engine manufacturer	Kawasaki
Motor/engine model	921V
Fuel tank volume	45.4 l
Fuel tank volume	12 gal (US)
EQUIPMENT	
12V outlet	No
Air filter type	Heavy-Duty Canister Style
All-Wheel Drive (AWD)	No
Anti-scalp wheels	6
Ball bearing wheels	No
Ball bearing front wheels	Yes
BioClip® kit	Not available as accessory (NOT AVAILABLE)
Blade brake clutch (BBC)	Yes
Blade engagement	Electric clutch
Blade type	High Performance
Blades	3 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	7-gauge fabricated
Cutting methods	Mulching/Side discharge
Deck lifting system	Manual, foot assisted
Deck Wash Port	No
Deflector	Included
Detachable transmission	Yes
Drive method	Lever-operated
Drive system	Rear wheel drive

Technical Specifications

Drive wheels	Rear
Electric start	Yes
Fan-cooled pumps	Yes
Front-End Protection	None
Handle type	Anti-vibration
Headlights	No
Hinged armrests	Standard
Hour meter type	Yes
Hydraulic equipment lift	No
Nose roller	No
Parking brake, type	Mechanical
Pivoting rear axle	No
Pneumatic drive	No
Reverse gearbox	No
Seat adjustment	Tool-less
Seat manufacturer	Seats Inc
Seat spring	Yes
Seat suspension	Yes
Seat type	Premium, suspension
Side adjustable handle	Yes
Throttle control	Yes
Track, rear	54.63 in
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel consumption	6.7 l
Fuel tank location	Side (Dual)
Fuel type, min (Europe)	87 Octane
Fuel type, min	87 octane
Oil capacity	1.9 l
Oil cooler	Yes
Oil filter	Yes
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	880 g
PET total	0 g
Plastic foil	525 g
Plastic rigid	355 g
Plastic total	880 g
Powder-coated cutting deck	Yes
PS/EPS/HIPS total	0 g
Rims, material	Steel
Rubber wheels	Included
Seat material	Vinyl
Spindle/mandrel type	Cast iron
PACKAGING	
Packaging, gross weight	136.1 kg
Packaging height	1346 mm
Packaging length	2299 mm
Packaging volume	6405.52 dm ³
Packaging width	2070 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	112 dB(A)
Sound pressure level at operators ear	80 dB(A)