



SUPER SF



AVAILABLE DECK SIZES
60" & 72"

| SUPER SF | |
|----------------------|--|
| ENGINE | |
| Manufacturer | Kawasaki FX Series, Vanguard Big Block™ |
| HP | 60", 72" deck: 38.5HP - FX1000 EFI 60", 72" deck: 40HP - Big Block™ EFI Oil Guard (Per SAE J1995) |
| Displacement | Kawasaki 999cc Vanguard 993cc |
| Cooling | Air cooled |
| Air Cleaner | Heavy duty air canister |
| Engine Warranty | 3-year |
| DRIVE SYSTEM | |
| Type | Dual hydrostatic |
| Pumps | Hydro-Gear 21cc |
| Wheel Motors | Parker TG |
| Hydraulic Cooling | Oil cooler w/ 8" fan |
| Reservoir Capacity | 6 quarts |
| Speed | Up to 15 mph (Using speed limiter: Up to 10 mph) |
| Parking Brakes | Hand operated drum brakes |
| DECKS | |
| Cutting Width | Side discharge: 60", 72" |
| Cutting Heights | 2.0"- 5.5" |
| Deck Lift | Electric actuator |
| Depth | 5.5" |
| Blades | 3 |
| Blade Length | 60" deck: 20.50" 72" deck: 24.50" |
| Blade Tip Speed | 60" deck: 18,400 72" deck: 19,300 |
| Spindles | Ductile cast iron with steel shafts and sealed ball bearings |
| Drive | Electric PTO clutch |
| Construction | 7 ga. w/ 7 ga. wrappers |
| Spindle Mounts | Reinforced 7 ga. stamped disc |
| Impact/Trim Areas | 11 ga. formed channel w/ rolled edge |
| Anti-scalp Wheels | n/a |
| CONSTRUCTION | |
| Frame | 1.5" x 3" steel tubing |
| Engine Plate | 7 ga. |
| Operator Platform | 7 ga. |
| Front Axle | Fabricated w/ tapered roller bearings |
| Front Caster Wheels | Tapered wheel bearings and debris cap |
| Front Caster Forks | Fabricated 1/2" steel |
| Operator Pad | Bolstered / Adjustable |
| GENERAL | |
| Fuel Capacity | 13.9 gallons |
| Front Tire | 13 x 6.5 - 6 semi pneumatic |
| Drive Tire | 26 x 12 - 12 |
| DIMENSIONS | |
| Weight | 60": 1450 lbs 72": 1500 lbs |
| Height | 50" |
| Length | 60": 79.2" 72": 81.7" |
| Width w/Chute Up | 60": 61.6" 72": 73.6" |
| Tire Width | 53.5" |
| Trim Side | 60": 4.1" 72": 12.5" |
| PRODUCTIVITY* | |
| Acres Per Hour | 60": 7.27 72": 8.73 |

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain. ** Specifications are subject to change without notice.

SUPER SF

Electric Actuator Deck Lift
Easily adjust your cutting height from 2.0" to 5.5".

60" and 72" VX Deck
7 ga. deckplate with 7 ga. stamped spindle mounts and a 11 ga. bull nose leading edge.

Kawasaki FX EFI and Vanguard EFI Oil Guard Engine
38.5 hp and 40 hp options.

Speed Control Bar Adjustment
Up to 15 mph with reduced speed up to 10 mph.



Semi Pneumatic Front Tires
13" front tires.

Hydro Oil Cooler
8" fan and 6-quart reservoir capacity.

Large Rear Tires
26" x 12" rear tires are larger than any other unit on the market.

Dual Fuel Tanks
13.9 gal. fuel capacity.



SUPER SF

- ✔ **Strong Hydro's**
Hydro-Gear 21cc pumps and Parker TG wheel motors
- ✔ **Service Friendly Design**
Designed to make maintenance and service fast and easy.
- ✔ **SmoothTrak™ Steering**
Precision control to help trim and maneuver easily around obstacles.
- ✔ **VX Deck**
Fabricated 7 ga. steel with 7 ga. wrappers engineered for extreme vacuum enhancing performance and cut quality.
- ✔ **26" Drive Tires**



ACCESSORIES

- ▶ Mulch kit
- ▶ Mesh side bagger (3 bushels)
- ▶ Mud Flap kit
- ▶ Light kit
- ▶ Stripe kit

