



# SUPER Z AND HYPERDRIVE



**SUPER Z**

**HYPERDRIVE**

AVAILABLE DECK SIZES  
**54"-72" 60"-72" RD**

AVAILABLE DECK SIZES  
**60"-72" 60"-72" RD**

	SUPER Z	HYPERDRIVE
<b>ENGINE</b>		
Manufacturer	Vanguard Big Block™, Kawasaki FX series	
HP	54", 60", 60" RD, 72" RD deck: 27HP - FX850 60", 66" & 72" deck: 35HP - FX1000 60" & 72" deck: 38.5HP - FX1000 EFI 60", 72" deck: 36HP - Big Block™ (Per SAE J1995)	60", 66", 72" deck: 40HP - Big Block™ EFI 60", 60"RD, 72" & 72" RD deck: 35HP - FX1000 60" & 72" deck: 40HP - Big Block™ EFI w/ Oil Guard 60" & 72" deck: 38.5HP - FX1000 EFI (Per SAE J1995)
Displacement	FX850: 852cc FX1000: 999cc FX1000 EFI: 999cc Vanguard: 993cc	Vanguard: 993cc Kawasaki: 999cc
Cooling	Air cooled	
Air Cleaner	Heavy Duty Canister	
Engine Warranty	Kawasaki: 3 year Vanguard: 5 year	
<b>DRIVE SYSTEM</b>		
Type	Dual hydrostatic	
Pumps	Hydro-Gear 21cc PY	Danfoss DDC-20
Wheel Motors	Parker TG	
Hydraulic Lines	Stainless Parker Seal-Loc Technology	
Reservoir Capacity	3 gallons	
Speed	Up to 14 mph	Up to 16 mph
Parking Brakes	Integrated with steering levers	
<b>DECKS</b>		
Cutting Width	Side discharge: 54", 60", 66", 72" Rear-discharge: 60", 72"	Side discharge: 60", 66", 72" Rear-discharge: 60", 72"
Cutting Heights	1" - 5.5"	
Deck Lift	Foot operated	
Depth	5.5"	
Blades	3	
Blade Length	54" deck: 18.50" 60" deck: 20.50" 66" deck: 22.50" 72" deck: 24.50"	60" deck: 20.50" 66" deck: 22.50" 72" deck: 24.50"
Blade Tip Speed	54"& 60": 18,600 66": 18,200 72": 18,500	60": 18,600 66": 18,200 72": 18,500 72"RD: 18,500
Spindles	Ductile cast iron with steel shaft and sealed ball bearings	
Drive	Electric PTO clutch	
Construction	Fabricated 7 ga.	
Spindle Mounts	Reinforced 7 ga. stamped disc	
Impact/Trim Areas	Front of deck: 11 ga. formed bump bar Side of deck: 1.5" x .375" steel bar	
<b>CONSTRUCTION</b>		
Frame	1.5" x 3" steel tubing	
Front Axle	Fabricated with tapered roller bearings	
Front Caster Wheels	Tapered wheel bearings and debris cap	
Front Caster Forks	Fabricated 1/2" steel	
<b>GENERAL</b>		
Seat	I3M suspension seat	
Fuel Capacity	11.7 gallons	
Cupholder	Yes	
Front Tire	13 x 6.5 - 6	
Drive Tire	54": 24 x 9.5 - 12 60", 66", 72": 24 x 12 - 12	26 x 12 - 12
<b>DIMENSIONS</b>		
Weight	54": 1420 lbs 60": 1451 lbs 60" RD: 1566 lbs 66": 1516 lbs 72": 1526 lbs 72"RD: 1626 lbs	60": 1536 lbs 60"RD: 1606 lbs 66": 1551 lbs 72": 1596 lbs 72"RD: 1676 lbs
Height	46.8" 72.5 w/ ROPs	
Length	54", 60": 89" 60"RD, 66": 91.5" 72", 72"RD: 93"	60": 89" 60"RD, 66": 91.5" 72", 72"RD: 93"
Width w/Chute Up	54": 60" 60": 66" 66"&72": 72" 72": 78" 72"RD: 73.23"	60": 66" 66"&72": 72" 72"RD: 78"
Tire Width	54": 53" 60", 60"RD: 57" 66", 72"RD, 72": 60"	60", 60"RD: 57" 66", 72"RD, 72": 60"
Trim Side	54": 2.4" 60": 3.4" 60"RD: 3.1" 66": 4.9" 72": 8.9"	60": 3.4" 60"RD: 3.1" 66": 4.9" 72": 8.9"
<b>PRODUCTIVITY*</b>		
Acres Per Hour	54": 6.11 60": 6.78 66": 7.46 72": 8.14	60": 7.76 66": 8.54 72": 9.31

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.  
\*\* Specifications are subject to change without notice.

# SUPER Z

## VX4 Deck

Fabricated 7 ga. steel deck engineered to move more grass at high speed while maintaining cut-quality.

## SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. Other brands have sensitive steering arms causing sudden and jerky movements.

## Commercial-grade Torque

Hydro-Gear 21cc PY pumps and Parker TG wheel motors.



## Foot Operated Deck Lift

Easily adjust the deck height between 1" - 5.5" with your foot.

## Easy to Service

Flip-up seat pan, removable floor pan, vented pulley covers.

## I3M Suspension Seat

High-back seat with adjustable armrests and 3-inch travel range.

## Kawasaki® FX & Vanguard Big Block™ Engines



## UPGRADES FOUND ON THE HYPERDRIVE

# HYPERDRIVE

- ✓ HyperDrive® Hydro System
- ✓ Optional Vanguard® Big Block™ Engine w/ Oil Guard (500 hour oil change)
- ✓ Danfoss DDC-20 Pumps
- ✓ Larger 26" Drive Tire
- ✓ Up to 16 mph (compared to 14 mph)



## HYPERDRIVE SYSTEM

Increase the life and performance of your mower with Hustler's exclusive HyperDrive system, the largest, most durable drive system in the industry. With temperature regulation and heavy-duty components, HyperDrive will keep you operating at peak performance.



9" Fan & High-Capacity Oil Cooler with Hot Oil Shuttle



Large Oil Reservoir



Heavy-Duty Parker TG280 Wheel Motors



Industrial-Grade Slipper Piston Pumps

## ACCESSORIES

- ▶ Steering extension kit
- ▶ Electric deck lift
- ▶ Rear hitch kit
- ▶ Anti-scalp deck rear wheels
- ▶ BacVac bagger
- ▶ Semi pneumatic front tire
- ▶ 3-bag powered bagger (12 bushels)
- ▶ Flex Forks®
- ▶ Mulch kit
- ▶ Light kit
- ▶ Sand kit
- ▶ Stripe kit
- ▶ Beacon kit
- ▶ Flasher kit
- ▶ Michelin® X® Tweel® Turf

## INDUSTRY'S BEST WARRANTY

