

COMMERCIAL ZTRAK™ MOWERS



JOHN DEERE

ZTrak™ Z900 Series EFI

INTRODUCING OUR NEW EFI MODELS

M Series: Z955M | Z965M | Z975M

R Series: Z955R | Z965R | Z985R

Six commercial-grade mowers join the ultra-durable Z900 Series lineup.

EFI engines offer several advantages, including improved fuel economy, optimal power output, and reduced emissions. Without throttle cables to break, they also enhance productivity. By adding an EFI mower to your fleet, you can save on fuel costs¹ and minimize downtime² without compromising performance.

Electronic Throttle Control

Consistent mowing speeds and better load pickup improve your productivity and cut quality on a variety of grass types.

Brake-N-Go System

Set the parking brake, turn the key, and get started in a snap.



Large Fuel Tank

Stay on the job longer before refueling with 11.5 U.S. gallons of fuel on board.

ComfortGlide™ Seating

Three deluxe seat options and a ComfortGlide™ suspension ensure superior comfort, even on bumpy terrain.

Airless Tire Options

Upgrade to optional Michelin X® TWEEL® Turf Airless Radial Tires and leave flats, patch kits, and downtime in the dust.

Mower Deck Options

Superior cut quality, easy blade changes, quick cleanup. Available in 7Iron™ PRO side-discharge, Mulch On Demand™, and FastBack™ PRO rear-discharge deck options.



Oil Guard™ System

Enjoy increased uptime with better oil filtration, a cooler running engine, and 500-hour service intervals. ROPS-mounted for easy access.



Easy Cut Adjustments

An easy-to-reach, 19-position dial lets you make fast height-of-cut changes from the comfort of your seat. Adjust in quarter-inch increments to match the terrain.



Electronic Fuel Injection (EFI)

Starts up fast and delivers consistent power, smooth performance, and increased fuel efficiency. Internal diagnostic readings keep machine maintenance on track.



Enhanced Digital Display

An upgraded digital display keeps operators informed with nine key maintenance indicators and an electronic fuel gauge.



Service ADVISOR™ Port

Analyze engine diagnostics in real time to isolate and resolve potential issues, and enable updates with dealer-installed connectivity.



Electronic Control Module (ECM)

Continuously matches the engine power to the cutting load, ground speed, and terrain for maximized cutting performance.



¹Internal testing comparing the Z955M 30.5-hp EFI and the Z960M 31-hp models indicated that the Z955M EFI model was 14.3% more fuel-efficient.
²Engines with Oil Guard™ 500-hour service interval.

Learn More
about ZTrak™ Mowers

COMPLETE Your Fleet.

ZTrak™ Z900 Series EFI SPECIFICATIONS

	M Series			R Series		
	Z955M EFI	Z965M EFI	Z975M EFI	Z955R EFI	Z965R EFI	Z985R EFI
ENGINE						
Engine Model	FX78IV EFI	6IA6 EFI	6IA7 EFI	FX78IV EFI	6IA6 EFI	6IG8 EFI
Certified Horsepower**	30.5 HP (22.7 kW), 822 cc	33.0 HP (24.6 kW), 993 cc	37.0 HP (27.6 kW), 993 cc	30.5 HP (22.7 kW), 822 cc	33.0 HP (24.6 kW), 993 cc	40.0 HP (29.8 kW), 993 cc
Oil Guard™	No	Yes	No	No	Yes	Yes
FUEL SYSTEM						
Fuel Tank Capacity	11.5 U.S. gal. (43.5 L)					
GROUND SPEED						
Ground Speed	12 mph (19.3 km/h)					
MOWER DECK						
7Iron™ PRO Side-Discharge	54 in. (137 cm) / 60 in. (152 cm)	60 in. (152 cm) / 72 in. (183 cm)	60 in. (152 cm) / 72 in. (183 cm)	60 in. (152 cm)	60 in. (152 cm) / 72 in. (183 cm)	72 in. (183 cm)
7Iron™ PRO Mulch On Demand	54 in. (137 cm) / 60 in. (152 cm)	N/A	60 in. (152 cm)	60 in. (152 cm)	N/A	N/A
7Iron™ PRO Rear-Discharge	60 in. (152 cm)	N/A	60 in. (152 cm) / 72 in. (183 cm)	72 in. (183 cm)	72 in. (183 cm)	72 in. (183 cm)
Height-of-Cut Range / Increment	1.0 in. to 5.5 in. (2.5 cm to 13.9 cm) – for all EFI / Carb Units	1.5 in. to 5.5 in. (3.8 cm to 13.9 cm) / 0.25 in. (0.64 cm)	1.5 in. to 5.5 in. (3.8 cm to 13.9 cm) / 0.25 in. (0.64 cm)	1.5 in. to 5.5 in. (3.8 cm to 13.9 cm) / 0.25 in. (0.64 cm)	1.5 in. to 5.5 in. (3.8 cm to 13.9 cm) / 0.25 in. (0.64 cm)	1.5 in. to 5.5 in. (3.8 cm to 13.9 cm) / 0.25 in. (0.64 cm)
ComfortGlide™	Standard	Standard	Standard	Standard	Standard	Standard
Seat Standard/Options	Deluxe Comfort Seat w/ Isolation (optional) Suspension Seat (optional)	Deluxe Comfort Seat w/ Isolation (optional) Suspension Seat (optional)	Deluxe Comfort Seat w/ Isolation (optional) Suspension Seat (optional)	Deluxe Comfort Seat w/ Isolation (optional)	Deluxe Comfort Seat w/ Isolation (optional)	Deluxe Comfort Seat w/ Isolation (optional)
WHEELS AND TIRES						
Drive Wheels	24x12-12 pneumatic 24x12-12 X TWEEL Turf (60")	24x12-12 pneumatic 24x12-12 XL TWEEL Turf (72")	24x12-12 pneumatic 24x12-12 X TWEEL Turf (60")	24x12-12 pneumatic 24x12-12 X TWEEL Turf (60") 24x12-12 XL TWEEL Turf (72")	24x12-12 pneumatic 24x12-12 XL TWEEL Turf (72")	24x12-12 pneumatic 24x12-12 XL TWEEL Turf (72")
Caster Wheel Type	13x6.5-6 flat free					
DIMENSIONS						
Machine Width (Chute Down)	68, 74 in. (172.7, 188 cm); rear discharge 63.5 in. (161.3 cm)	74, 86 in. (188, 218.4 cm)	74, 86 in. (188, 218.4 cm); rear discharge 63.5, 75.8 in. (161.3, 192.5 cm)	74 in. (188 cm); rear discharge 75.8 in. (192.5 cm)	74, 86 in. (188, 218.4 cm); rear discharge 75.8 in. (192.5 cm)	86 in. (218.4 cm); rear discharge 75.8 in. (192.5 cm)
WARRANTY³						
Duration	36 months or 1200 hours, whichever comes first. First 24 months, no hour limitation.	36 months or 1200 hours, whichever comes first. First 24 months, no hour limitation.	36 months or 1200 hours, whichever comes first. First 24 months, no hour limitation.	36 months or 1200 hours, whichever comes first. First 24 months, no hour limitation.	36 months or 1500 hours, whichever comes first. First 24 months, no hour limitation.	36 months or 1500 hours, whichever comes first. First 24 months, no hour limitation.
OPERATIONS CENTER COMPATIBLE						
	Yes	Yes	Yes	Yes	Yes	Yes

³All ZTrak™ 900 Series EFI M Series Mowers come with a 36 month/1200-hour machine warranty. All ZTrak™ 900 Series EFI R Series Mowers come with a 36 month/1500-hour machine warranty. For full details, see the LIMITED WARRANTY FOR NEW JOHN DEERE TURF AND UTILITY EQUIPMENT at JohnDeere.com or JohnDeere.ca/TUWarranty.



Z955M EFI



Z965M EFI



Z975M EFI



Z955R EFI



Z965R EFI



Z985R EFI

