

100" OF POWER, PRODUCTION, AND PRECISION WZ800 FLEX DECK ZERO TURN MOWER


NEW!
Signature
MODEL
WZ800
100" WIDTH
OF CUT



CONTOURS ROLLING TERRAIN

**FIVE 21" FLEX DECKS
ELIMINATES SCALPING
ACCURACY OF A 21" PUSH MOWER**

Four things set the Lastec WZ800 Articulator apart from any other mower on the planet. First, the **flex deck zero turn mower cuts 100" of grass**. Second, it cuts that wide with the **accuracy of a 21" push mower**. Third, the WZ800 can fold the outer decks with ease, reducing the **transport width to 78"**. Fourth, it can safely trim closer to ponds, banks and other obstacles than other mowers with it's 21" outside deck side reach. Tough enough for Commercial applications without compromising cut quality.

UP TO **7.27** ACRES PER HOUR

Average speed of 8 mph,
assumed 10% overlap
and no stops

**BUILT
* IN THE *
USA**



DIMENSIONS & WEIGHT*

Length	92"
Width	(mowing) 119"
Width	(transport) 78"
Height	(ROPS up) 82"
Height	(ROPS down) 57"
Wheelbase	54"
Rear Track	60"
Weight	

TRACTION SYSTEM

Max Forward Speed	Infinitely variable - 10mph (16.09 km/h)
Max Reverse Speed	Infinitely variable - 3mph (4.83 km/h)
Front Tires	Two 13 x 6.5-6, smooth, semi-solid
Rear Tires	Two 26 x 12-12, 6-ply, turf tread
Parking Brake	Lever Actuated, 2 mechanical drum-type on rear wheels
Steering	Dual-lever hydrostatic differential type with rear wheels
Hydraulic Oil Filters	Full-flow, replaceable spin-on type
Hydraulic Oil Cooler	Pressurized, forced-air

ENGINE

Type	37 hp, Kubota® D1803-CR-E4B 3-cylinder, naturally aspirated, liquid-cooled diesel
Emissions Level	EPA Tier 4 final, stage IIIB
Rated Horsepower	37.6 hp (SAE J1995)
Displacement	111.4 cu. in.
Air Cleaner	6" dual element, dry cartridge
Cooling System Type	Pressurized radiator, forced circulation with water pump
Alternator Capacity	12V, 60A
Oil System Type	Forced lubrication by trochoid pump
Oil Capacity	1.85 U.S. gal
Oil Filter Type	Full-flow, replaceable spin-on type
Fuel Capacity	18 gallons, dual 9 gallon (34.07 liter) self-leveling tanks

FEATURES & BENEFITS

- Five 21" (533.4 mm) flex/articulating rotary cutting decks with 100" (2.54 m) cutting width.
- Side, rear and mulching discharge capabilities.
- 20" side reach allows close trimming near ponds, banks, ditches and other obstacles.
- The highest cut accuracy and quality available.
- Heavy duty hydrostatic drive.
- Lightweight, low center of gravity.
- 18 gallons, dual 9 gallon (34.07 liter) self-leveling tanks.
- No tools required to change height in the field.

CUTTING DECK SYSTEM

Cut Width	100" (2.54m)
Blades	Five 21" high lift
Deck Segments	Five 21" (533.4 mm) articulating, 5.5" deep, 7ga welded pans
Height of Cut Range	1"-4.5" in ¼" increments
Height Adjustment	Manual with spacers (9 adjustment points)
Acres per Hour	7.27 (assumes 10% overlap, no stops, and average speed of 8 mph)
Transport Lift Type	Two electric-over-hydraulic actuators
Deck Caster Wheels	Eight 11 x 4-5, smooth, no-flat
Blade Tip Speed	18,500 FPM (approximate)

LASTEC 30 YEARS
ARTICULATORS ART OF MOWING

800.515.6798



lastec.com

ARTICULATION

Lastec's flex decks allow you to approach contours from any angle without turf damage or scalping caused by traditional fixed decks.

12° of articulation up/down for each deck



UP TO **7.27** ACRES PER HOUR

Average speed of 8 mph, assumed 10% overlap and no stops