

WZ600 OFFSET FLEX DECK DESIGNED TO MINIMIZE HAND TRIMMING & MOWING


NEW!
Signature
**MODEL
WZ600**
80" OFFSET
WIDTH OF CUT



OFFSET ROTARY FLEX DECK

**FOUR 21" FLEX DECKS
ELIMINATES SCALPING
ACCURACY OF A 21" PUSH MOWER**

UP TO **5.82** ACRES PER HOUR

Average speed of 8 mph,
assumed 10% overlap
and no stops



The WZ600 is built to meet the rotary demands that range from **golf course use to heavy commercial applications**. This unit is available with a 37 hp Kubota diesel. The WZ600 offers a wide cut utilizing **four 21" (533.4 mm) flex rotary decks** and features a 20" (508 mm) side reach to **reduce hand mowing and trimming** near ponds or banks. Tough enough for commercial applications without compromising cut quality.

DIMENSIONS & WEIGHT*

Length	92"
Width	(mowing) 80"
Width	(transport) 70"
Height	(ROPS up) 82"
Height	(ROPS down) 57"
Wheelbase	54"
Rear Track	60"
Weight	

TRACTION SYSTEM

Max Forward Speed	Infinitely variable - 10mph (16.09 km/h)
Max Reverse Speed	Infinitely variable - 3mph (4.83 km/h)
Front Tires	Two 13 x 6.5-6, smooth, semi-solid
Rear Tires	Two 26 x 12-12, 6-ply, turf tread
Parking Brake	Lever Actuated, 2 mechanical drum-type on rear wheels
Steering	Dual-lever hydrostatic differential type with rear wheels
Hydraulic Oil Filters	Full-flow, replaceable spin-on type
Hydraulic Oil Cooler	Pressurized, forced-air

ENGINE

Type	37 hp, Kubota® D1803-CR-E4B 3-cylinder, naturally aspirated, liquid-cooled diesel
Emissions Level	EPA Tier 4 final, stage IIIB
Rated Horsepower	37.6 hp (SAE J1995)
Displacement	111.4 cu. in.
Air Cleaner	6" dual element, dry cartridge
Cooling System Type	Pressurized radiator, forced circulation with water pump
Alternator Capacity	12V, 60A
Oil System Type	Forced lubrication by trochoid pump
Oil Capacity	1.85 U.S. gal
Oil Filter Type	Full-flow, replaceable spin-on type
Fuel Capacity	18 gallons, dual 9 gallon (34.07 liter) self-leveling tanks

FEATURES & BENEFITS

- Four 21" (533.4 mm) flex/articulating rotary cutting decks with 80" (2.03 m) cutting width.
- Side and mulching discharge capabilities.
- 20" side reach allows close trimming near ponds, banks, ditches and other obstacles.
- The highest cut accuracy and quality available.
- Heavy duty hydrostatic drive.
- Lightweight, low center of gravity.
- 18 gallons, dual 9 gallon (34.07 liter) self-leveling tanks.
- No tools required to change height in the field.

CUTTING DECK SYSTEM

Cut Width	80" (2.03m)
Blades	Four 21" high lift
Deck Segments	Four 21" (533.4 mm) articulating, 5.5" deep, 7ga welded pans
Height of Cut Range	1"-4.5" in ¼" increments
Height Adjustment	Manual with spacers (9 adjustment points)
Acres per Hour	5.82 (assumes 10% overlap, no stops, and average speed of 8 mph)
Transport Lift Type	Two electric-over-hydraulic actuators
Deck Caster Wheels	Eight 11 x 4-5, smooth, no-flat
Blade Tip Speed	18,500 FPM (approximate)



800.515.6798



lastec.com

ARTICULATION

Lastec's flex decks allow you to approach contours from any angle without turf damage or scalping caused by traditional fixed decks.

12° of articulation up/down for each deck



UP TO **5.82** ACRES PER HOUR

Average speed of 8 mph, assumed 10% overlap and no stops