

INTRODUCING THE WORLD'S LARGEST ZERO TURN FLEX DECK MOWER


NEW!
Signature
MODEL
WZ1000
120" WIDTH
OF CUT

120" CUTTING WIDTH THAT
CONTOURS ROLLING TERRAIN

FIVE 25" FLEX DECKS ■ ELIMINATES SCALPING
ACCURACY OF A 25" PUSH MOWER

Featuring a **MASSIVE 120" cutting width**, the WZ1000 is the world's biggest zero turn mower with the **accuracy of five small push mowers**. Built in the USA, the WZ1000 includes five 25" fully articulating flex decks for superior cut quality, quick fold electric decks for transport or storage, and patented belt driven decks for minimal maintenance and **unmatched fuel efficiency**. With the 120" cutting width, zero-turn accuracy, and up to 10 mph speed, the **WZ1000 is 15% more productive than a 104" zero turn mower**. Perfect the Art of Mowing today with the 120" wide WZ1000 Zero Turn Mower that **minimizes investment, maintenance, and man-power** while maximizing cut quality, productivity, and performance.

UP TO **8.73** ACRES PER HOUR
Average speed of 8 mph,
assumed 10% overlap
and no stops



**BUILT
IN THE
USA**

DIMENSIONS & WEIGHT*

Length	92"
Width	(mowing) 138"
Width	(transport) 94"
Height	(ROPS up) 82"
Height	(ROPS down) 57"
Wheelbase	54"
Rear Track	60"
Weight	

TRACTION SYSTEM

Max Forward Speed	10 mph
Max Reverse Speed	6 mph
Front Tires	Two 13 x 6.5-6, smooth, semi-solid
Rear Tires	Two 26 x 12-12, 6-ply, turf tread
Parking Brake	Two mechanical drum-type on rear wheels
Steering	Dual-lever hydrostatic differential type with rear wheels
Hydraulic Oil Capacity	
Hydraulic Oil Filters	Full-flow, replaceable spin-on type
Hydraulic Oil Cooler	Pressurized, forced-air

ENGINE

Type	Kubota® D1803-CR-TE4B 3-cylinder, turbo-charged, liquid-cooled diesel
Emissions Level	EPA Tier 4 final, stage IIIB
Rated Horsepower	49.6 hp (SAE J1995)
Displacement	111.4 cu. in.
Air Cleaner	6" dual element, dry cartridge
Cooling System Type	Pressurized radiator, forced circulation with water pump
Alternator Capacity	12V, 60A
Oil System Type	Forced lubrication by trochoid pump
Oil Capacity	1.85 U.S. gal
Oil Filter Type	Full-flow, replaceable spin-on type
Fuel Capacity	17 U.S. gallons

FEATURES & BENEFITS

- Five 25" (635 mm) flex/articulating rotary cutting decks with 120" (3 m) cutting width.
- Side, rear and mulching discharge capabilities.
- 27" (685.8 mm) side reach allows close trimming near ponds, banks, ditches and other obstacles.
- The highest cut accuracy and quality available.
- Heavy duty hydrostatic drive.
- Lightweight, low center of gravity.
- Two 8.5 gallon fuel tanks.
- No tools required to change height in the field.

CUTTING DECK SYSTEM

Cut Width	120"
Blades	Five 25" high lift
Deck Segments	Five articulating, 7ga welded construction
Height of Cut Range	1"-4.5" in ¼" increments
Height Adjustment	Manual with spacers (9 adjustment points)
Acres per Hour	8.73 (assumes 10% overlap, no stops, and average speed of 8 mph)
Transport Lift Type	Two electric-over-hydraulic actuators
Deck Caster Wheels	Eight 11 x 4-5, smooth, no-flat
Blade Tip Speed	18,500 FPM (approximate)

LASTEC **30**
ARTICULATORS ART OF MOWING YEARS


800.515.6798



lastec.com

ARTICULATION

Lastec's flex decks allow you to approach contours from any angle without turf damage or scalping caused by traditional fixed decks.



12° of articulation up/down for each deck



UP TO **8.73** ACRES PER HOUR

Average speed of 8 mph, assumed 10% overlap and no stops